Codelock

Access Control





- One lock with two codes
- Sturdy construction for outdoor and indoor use
- Best selling codelock in the world

The V42 is the best-selling codelock in the world. It is compact and easy to use with a modern design that is suitable for either indoor or outdoor mounting. The V42 has a capacity of two four-digit codes. One can be used by residents while the other is used by the property care taker, for example. All settings are made directly in the unit.



Technical Data

	V42		
Operating voltage	12 to 24 VAC/DC		
Current consumption	8 mA in standby		
Inputs	Exit button requests with delay. Two separate for code disable.		
Outputs	Voltage-free relay contact, max. 1 A, 28 VDC.		
Opening time	1–30 sec.		
Door capacity	1		
Code capacity	Two four-digit codes		
Operating temperature	-35 to +55 °C		
Environment	Indoor or outdoor use (IP54 design). In very exposed locations, use SH2 or SH1 rain cover.		
IP rating	IP54		
Housing	Cast metal with stainless steel buttons and security lock		
Colour	Grey		
Dimensions (W x H x D)	80 x 140 x 40 mm		

Details for ordering

Туре	Part no	Designation	Weight
V42	V24246-C3552-A1	Codelock with two codes	0.72 kg

The information in this document contains general descriptions of technical options available, which do not always have to be present in individual cases. The required features should therefore be specified in each individual case at the time of closing the contract.

© Vanderbilt International (IRL) Ltd. • Document no. A-100190-1 • Edition: 2015-06-15 • Document version: 1.0

Vanderbilt International (IRL) Ltd. Clonshaugh Business and Technology Park Clonshaugh Dublin 17 Ireland